

BTM-510B

Bluetooth Wireless Microphone System

- 18ms Low Latency with 48KHz/16 bits high quality wireless audio transmission.
- Linear range up to 20m for unlimited movements.
- Two transmission methods for high range or save power.
- Frequency Hopping Spread Spectrum provides transmission safety.

BTM-510B

Bluetooth Wireless Microphone System

BTM-510B Bluetooth Wireless Microphone System

Low Latency Bluetooth Module



BTM-510BD+BTM510BR for Dynamic Microphone

Wireless transmission: BLE (Bluetooth Low Energy) 5.1

Carrier Frequency: ISM band 2.400~2.480GHz

Operation Range: At least 20m (Straight line distance)

Latency: 18ms

Transmission Power: +10dBm

RF Sensitivity: -94dBm

Power Supply: AAA size x 4 (Receiver x2, Transmitter x2)

Battery Life: Up to 8hrs (Alkaline battery)

Input Jack: 3P-XLR female plug

Output Jack: Ø6.3 mm male plug

Dimensions (L x W x H): 98.6 × 26 × 28.3 mm (BTM-510BD)

116.9 × 26 × 28.1 mm (BTM-510BR)

Weight (without batteries): 35g(BTM-510BD)

25g(BTM-510BR)



BTM-510BC+BTM510BR for Condenser Microphone

Wireless transmission: BLE (Bluetooth Low Energy) 5.1

Carrier Frequency: ISM band 2.400~2.480GHz

Operation Range: At least 20m (Straight line distance)

Latency: 18ms

Transmission Power: +10dBm

RF Sensitivity: -94dBm

Power Supply: AAA size x 4 (Receiver x2, Transmitter x2)

Battery Life: Up to 8hrs (Alkaline battery)

Input Jack: Ø3.5 mm female plug

Output Jack: Ø6.3 mm male plug

Dimensions (L x W x H): 92.9 × 26 × 28.1 mm (BTM-510BC)

116.9 × 26 × 28.1 mm (BTM-510BR)

Weight (without batteries): 23g(BTM-510BC)

25g(BTM-510BR)



TAIWAN CAROL ELECTRONICS CO., LTD.

Tel:+886-4-22347677 Fax:+886-4-22348698

E-mail:carol@taiwancarol.com

www.taiwancarol.com

